

Vertical UK PDU's

- 3-metre 1.5mm lead
- Tough 1.5U aluminium extrusion
- Shrouded switch with switch cover
- C14, C20, Schuko, or 16A commando options
- Vertical UK 13A BS1363 'type G' outlets


Vertical UK PDUs are widely used to accommodate cabinets where a higher number of UK sockets are needed but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical harware

Standard products

Order Code	*Product Description*
V13A/4	4-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/5	5-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/6	6-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/6/RH	6-way UK 13A right hand socket PDU, switch to 3m lead to 13A plug
V13A/8	8-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/10	10-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/12	12-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/12/RH	12-way UK 13A right hand socket PDU, switch to 3m lead to 13A plug
V13A/16	16-way UK 13A power with switch to 3-metre lead to 13A plug
V13A/20	20-way UK 13A power with switch to 3-metre lead to 13A plug

PDU options

 IEC C14

 IEC C20

 16A commando

PDU technical data

Weight of PDU	0.95kg – 1.9kg
Net length of PDU	490mm – 1090mm
Net width of PDU	60mm
Net depth of PDU	45mm
Shipping length of PDU	515mm – 1420mm
Shipping Width of PDU	150mm
Shipping Depth of PDU	70mm
Shipping Weight of PDU	1.1kg – 2.4kg
PDU max power	3250W
Output rating	13A
Overall rating	16A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC