

Description


Multimode pigtails are used to connect high speed networks like Gigabit Ethernet, Fast Ethernet and Ethernet. Our multimode pigtail buffer conforms to IEC, EIA TIA and Telecordia standards. They are terminated with our standard connector which gives optimum optical performance.

Features & Benefits

- SC, LC, ST, FC connectors
- Low smoke zero halogen (LSZH) buffer
- 900µm tight buffer or easy strip
- OM4 pigtail is available in standard aqua colour
- Multimode fibre conforms to ITU-G651, TIA/EIA 492AAAA
- Different connector performance range for specific application
- Available in standard 12 colours as per IEC 60304
- Available in standard and blister packing

Applications

- Networks including Ethernet, Fast Ethernet and GBE
- Internal inter-connect
- Ideal for a wide range of telecom, datacom and process control applications where ruggedisation is required
- Suitable for repeated handling in patch panels and racks



Connector Specification

OPTICAL PERFORMANCE	MULTIMODE	CONFORMANCE
IL Max/Master (Acceptance)	0.25 dB	IEC 61300-3-4
Ave/Master	0.15 dB	IEC 61300-3-4
Ave/Random	0.20 dB	IEC 61300-3-34

Cable Specification

CHARACTERISTICS	UNITS	SIMPLEX
Crush	N/100mm	500
Operating Temperature	°C	-20 to 60
Nominal buffer Diameter	µm	900+50
Max Tensile Load	N	6

Fibre Specification

CHARACTERISTICS		
Attenuation (dB) / km	2.8 @ 850nm / 0.8 @ 1300nm	
Bandwidth OFL (MHz x km)	3500 @ 850nm / 500 @ 1300nm / 4700 @ 850nm	

Part Number Generator

PREFIX	CONNECTORS	MODEL	LENGTH
FP	18	04	1S
	ST = 15 SC = 16 FC = 17 LC = 18	OS2 = 01 OM1 = 03 OM2 = 02 OM3 = 04 OM4 = 05	1S (Simplex) 2S (Simplex)